



# BOXER™

**A lot of Water Fast, at the Right Temperature, When You Don't Have Time to Waste!**

Meet Boxer™! Ideal for emergency drench shower and eyewash applications, Boxer™ delivers the knock-out punch by providing endless reliable tepid water with 3.0 to 30.0 gpm flow rates. Compliant with ANSI Z358.1.



# BOXER™

Chronomite ERB Series heaters are designed with multiple activations. **Low activation** is ideal for Emergency Safety Eyewash/Facewash combination with Drench Shower. The **Standard activation** is ideal for Commercial and Industrial tank heating. The **High activation** model is designed to work with Emergency Safety Drench Shower Equipment.

## Features and Benefits:

- Digital microprocessor provides ultra quick response time, controlling hot water temperatures 120x per second. Eliminates concern of scalding and the need for mixing valves.
- Several models available with power up to 154 KW and flow ranges from 3 to 30 gpm.
- 99% energy efficient for water and energy savings.
- Rugged stainless steel construction.
- Can provide 84° tepid water to meet ANSI Z358.1.

### CHRONOMITE - BOXER™ - 3 PHASE - LOW ACTIVATION

Dimensions:	26-3/4" x 21" x 7-1/2"
Weight:	76 LBS
Materials:	Rugged stainless steel housing Celcon plastic element assembly with Nichrome coils
Minimum Operating Flow Rate:	3.0 GPM
Minimum Operating Pressure:	25 PSI
Maximum Operating Pressure:	80 PSI
Maximum Pressure:	150 PSI
Maximum Operating Temperature:	160°F
Listing:	UL, UPC

#### GENERAL NOTES:

- The microprocessor adjusts the heater's power for variations in flow rates, inlet water temperature and pressure to assure the selected water temperature
- 240V models when operated at 220V will have approximately a 15% wattage decrease
- For EFD units - order ERB-L9 series option (F) with 84°F water

